Description

Clysar ® EVO-C™ Confidential film is a tough, strong, opaque polyolefin shrink film made with Post-Consumer Recycled (PCR) content and prequalified for the How2Recycle® Store Drop-Off label. Ideal for confidential shipping and product containment, the versatile film offers UV protection and a high degree of puncture, tear and abrasion resistance.

A replacement for most non-recyclable shrink films or corrugate, Clysar ® EVO-C™ Confidential film conforms to irregular shapes and seals reliably on a wide range of shrink equipment. The film offers a sustainable, cost-effective overwrap or secondary shipping material for applications requiring flexible sizing, security, privacy and product protection.



Prequalified for the **How2Recycle**® Store Drop-Off Label

Clysar, LLC

888-4-CLYSAR marketing@clysar.com

Highway 67 South Clinton, IA 52732

www.clysar.com



Clysar® EVO-C™ Confidential Film DATA SHEET

Uses

Clysar® EVO-C™ Confidential film is a market-leading sustainable security and shipping film. It is made with post-consumer recycled content and is prequalified for recycling in the Store Drop-Off stream by **How2Recycle**®.

The right-gauged opaque film delivers 90% opacity, UV-blocking properties and effective concealment, while using 30% less packaging material.

Applications include high-value products such as jewelry or electronics;

Use to conceal and protect products shipped in an overbox or replace the outer shipping box completely.

sensitive printed or personalized materials; pharmaceuticals and completely. supplements; official documents and forms; books, catalogs and magazines; gourmet foods; footwear; sporting goods; and liquid or granular cleaning, personal care and household products.

Significant Features

Sustainability

- Made with Post-Consumer Recycled (PCR) content certified by SCS Global Services.
- Prequalified for Store Drop-Off by How2Recycle®.



A sustainable and cost-saving alternative to bulky corrugate boxes.

- Provides 30% right-gauged solution over 150-gauge concealment films.
- Delivers significant material reduction, lowers DIM weight in comparison to corrugate.
- Requires less energy/lower temperature settings on sealers and shrink tunnels.

Sealing

- Provides strong, durable seals with most sealing systems.
- Wide sealing temperature range.
- Requires little or no cooling dwell.

Shrinking

- Excellent cleanup for tight, attractive packages.
- High shrink force conforms to irregular shapes, offers excellent bundling capability.
- Excellent resistance to burn-through.

General

- Delivers 90% opacity, blocking nearly 100% of UV light.
- Easy to run on most types of shrink equipment.
- Ultra-strong, puncture-, abrasion- and tear-resistant.
- May be printed or used with labels.

FDA/USDA Status

Clysar® films sold by Clysar, LLC, for food packaging use comply with U.S. Food and Drug Administration (FDA) requirements under the Federal Food, Drug and Cosmetic Act as amended. Clysar complies with FDA regulation 21 CFR 177.1520— Olefin polymers, allowing use for articles that contact food, except for articles used for packing or holding food during cooking.

Use

Clysar, LLC, does not recommend using traditional heating or cooking methods for foods wrapped in Clysar® shrink films. For conditions specific to microwave cooking, please request documentation that is specific for your application through your Clysar representative.

Disposal

Preferred options for disposal are: (1) Store drop-off recycling; and (2) incineration with energy recovery.

Storage

Storage below 32°C (90°F) is recommended. Prolonged exposure to temperatures moderately above 32°C (90°F) or brief exposure to temperatures well above 32°C (90°F) may cause difficulty in unwinding film.

For more detailed information on the safe handling of Clysar® films, a "Safety in Handling and Use" guide can be obtained from your Clysar representative.

Clysar, LLC

888-4-CLYSAR marketing@clysar.com

Highway 67 South Clinton, IA 52732

www.clysar.com



Standard Put-Ups

- 100 Gauge (90% Opacity for Privacy)
- Flat film is available in custom widths ranging from 3" up to 80" in 1/4" increments.*
- Folded film is available in custom widths from 3" up to 37" in ½" increments.*
- Folded film will have half the linear footage of flat film for same gauge and roll dimensions.

Shipping

Clysar® EVO-C™ Confidential film can be packaged in corrugate-free packaging (singles, efficiency or cradle pack) to support sustainability throughout the supply chain.

Summary of Properties

Clysar® EVO-C™ Confidential - Linear Footage Flat Film (Table 1)

Core I.D., in.	Roll O.D., in.	100 Gauge	
3	10 1/2	5,250	
3	14 1/2	10,500	
6	12 1/2	5,250	
6	15	10,500	

Typical Properties of Clysar® EVO-C™ Confidential (Table 2)

Property	ASTM Test Method	Unit	100 Gauge
Haze	D1003	%	NA
Gloss at 20°	D2457	(photocell)	75
Transmittance	D1003-13	%	10
COF, Kinetic	D1894	-	0.20
Shrink Force	D2838	g/in@100°C	105
Stiffness Modulus (avg)	D882	kpsi	85
Tensile Strength (avg)	D882	kpsi	14.9
Elongation (avg)	D882	%	118
Tear Strength (avg) (Elmendorf)	D1922	g	18
Spencer Impact	D3420	in-lbs	4

Note: These values are typical data for EVO-C™ Confidential shrink film and are not intended for use as limiting specifications.

UV Status

Verified to block nearly 100% of UV light through independent lab testing.

Recyclability

Clysar® EVO-C™ Confidential shrink film is approved for the Store Drop-Off label by **How2Recycle®**, and has obtained an official letter of pregualification.





Made with Post-Consumer Recycled (PCR) content certified by SCS Global Services.

The technical data contained herein are guides to the use of Clysar* films. The advice contained herein is based upon tests and information believed to be reliable, but users should not rely upon it absolutely for specific applications because performance properties will vary with processing conditions. It is given and accepted at user's risk, and confirmation of its validity and suitability in particular cases should be obtained independently. Clysar makes no guarantees of results and assumes no obligations or liability in connection with its advice. This publication is not to be taken as a license to operate under, or recommendation to infringe, any patents. CAUTION: Do not use in medical applications involving permanent implantation in the human body. For other medical applications, see Clysar Medical Caution Statement, MCS 02.

^{*}Contact your Clysar representative for details.